

RECEIVED
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

MAILED IN TRIPPLICATE
Other instructions on
reverse side

Form approved.
Budget Bureau No. 1004-0136
Expires August 31, 1985

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. TYPE OF WORK

DRILL ☒

DEEPEN ☐

PLUG BACK ☐

b. TYPE OF WELL

OIL
WELL ☒

GAS
WELL ☐

OTHER

SINGLE
ZONE ☒

MULTIPLE
ZONE ☐

2. NAME OF OPERATOR

Wildrose Resources Corporation

PH: 303-770-6566

3. ADDRESS OF OPERATOR

4949 South Albion Street, Littleton, CO 80121

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)*

At surface

1980' FSL & 1843' FEL (NW $\frac{1}{4}$ SE $\frac{1}{4}$)

At proposed prod. zone

Same

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE*

21 miles SE of Myton, Utah

15. DISTANCE FROM PROPOSED*

LOCATION TO NEAREST
PROPERTY OR LEASE LINE, FT.
(Also to nearest drlg. unit line, if any)

1843'

16. NO. OF ACRES IN LEASE

1200

17. NO. OF ACRES ASSIGNED
TO THIS WELL

40

18. DISTANCE FROM PROPOSED LOCATION*
TO NEAREST WELL, DRILLING, COMPLETED,
OR APPLIED FOR, ON THIS LEASE, FT.

None

19. PROPOSED DEPTH

5700'

20. ROTARY OR CABLE TOOLS

Rotary

21. ELEVATIONS (Show whether DF, RT, GR, etc.)

4931' GR

22. APPROX. DATE WORK WILL START*

September 15, 1996

23.

PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
12-1/4"	8-5/8"	24#, J-55	300'	225 sx
7-7/8"	5-1/2"	15.5#, J-55	5700'	800 sx

SEE ATTACHED EXHIBITS:

A - Surveyors Plat

E - Access Road Map

B - 10 Point Plan


F - Production Facilities

C - BOP Diagram

G - Existing Wells Map

D - 13 Point Surface Use Program

H - Pit & Pad Layout, Cuts & Fills,
Cross Sections, Rig Layout



IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24.

SIGNED

Kay J. Keltner

TITLE

Vice President

DATE

August 13, 1996

(This space for Federal or State office use)

PERMIT NO.

43-047-32781

APPROVAL DATE

APPROVED BY

J. Matthews

TITLE

Petroleum Engineer

DATE


9/5/96

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions On Reverse Side

**WILDROSE RESOURCES CORP.
WELL LOCATION PLAT
TROON FEDERAL #33-14**

LOCATED IN THE NW1/4 OF THE SE1/4 OF
SECTION 14, T9S, R18E, S.L.B.&M.




SCALE: 1" = 1000'

LEGEND AND NOTES

- ◇ ORIGINAL MONUMENTS FOUND AND USED
BY THIS SURVEY.

THE GENERAL LAND OFFICE (G.L.O.) PLAT WAS
USED FOR REFERENCE AND CALCULATIONS AS
WAS THE U.S.G.S. QUADRANGLE MAP.

THIS SURVEY WAS PERFORMED USING GLOBAL
POSITIONING SYSTEM PROCEDURES AND EQUIPMENT




SURVEYOR'S CERTIFICATE

I HEREBY CERTIFY THAT THIS PLAT WAS PREPARED
FROM FIELD NOTES OF AN ACTUAL SURVEY
PERFORMED BY ME, DURING WHICH THE SHOWN
MONUMENTS WERE FOUND OR ESTABLISHED.

Jerry D. Allred
JERRY D. ALLRED, REGISTERED LAND SURVEYOR,
CERTIFICATE NO. 148951 (UTAH)

Exhibit 'A'



JERRY D. ALLRED & ASSOCIATES
SURVEYING CONSULTANTS
121 NORTH CENTER STREET
P.O. BOX 975
DUCHESNE, UTAH 84021
(801)-738-5352

2 AUG 1996

83-123-026

EXHIBIT B

WILDROSE RESOURCES CORPORATION
TROON FEDERAL #33-14
LEASE #U-74405
NW/SE SECTION 34, T9S, R18E
UINTAH COUNTY, UTAH

TEN POINT COMPLIANCE PROGRAM OF APPROVAL OF OPERATIONS

1. The Geologic Surface Formation

The surface formation is the Uintah (Tertiary).

2. Estimated Tops of Important Geologic Markers

Green River	1100'
Wasatch Tongue of Green River	5600'
Total Depth	5700'

3. Estimated Depths of Anticipated Water, Oil, Gas or Minerals

No water bearing zones are anticipated

Green River 4000' - 5700' Oil

4. The Proposed Casing Program

<u>HOLE</u>	<u>INTERVAL</u>	<u>LENGTH</u>	<u>SIZE(OP)</u>	<u>WEIGHT, GRADE, JOINT</u>	<u>NEW OR USED</u>
12.25"	0 - 300'	300'	8-5/8"	24# K-55 ST&C	New
7-7/8"	0 - 5700'	5700'	5-1/2"	15.50# J-55 ST&C	New

Cement Program -

Surface Casing: 225 sacks Class "G" plus 2% CaCl₂

Production Casing: 200 sacks Lite Cement and 600 sacks Class "G" with additives

5. The Operator's Minimum Specifications for Pressure Control

EXHIBIT "C" is a schematic diagram of the blowout preventer equipment. A 2M system will be used. The blind rams and the pipe

Accessories to BOP will include an upper kelly cock, floor safety valve, drill string BOP and choke manifold with pressure rating equivalent to the BOP stack.

Mud system will be 2% KCl water with adequate stocks of sorptive agents on site to handle possible spills of fuel and oil on the surface. Heavier muds will be available to be added if pressure requires.

7. The Auxiliary Equipment to be Used

- ## 8. The Testing, Logging and Coring Programs to be Followed

- a) No Drill Stem Tests will be run.
- b) The Logging Program: Dual Later Log 300' - T.D.
Formation Density-CNL 4000' - T.D.
- c) No coring is anticipated.
- d) Stimulation procedures will be determined after evaluation of logs. If treatment is indicated, appropriate Sundry Notice will be submitted for approval.

9. Any Anticipated Abnormal Pressures or Temperatures

No abnormal pressures or temperatures have been noted or reported in wells drilled in the area nor at the depths anticipated in this well. Bottom hole pressure expected is 1500 psi + or -.

No hydrogen sulfide or other hazardous fluids or gases have been found, reported or known to exist at these depths in the area.


10. Anticipated Starting Date and Duration of the Operations.

The anticipated starting date is September 15, 1996. Operations will cover approximately 10 days for drilling and 14 days for completion.

Hazardous Chemicals

No chemicals subject to reporting under SARA title III in an amount equal to or greater than 10,000 pounds will be used, produced, stored, transported or disposed of annually in association with the drilling of this well. Furthermore, no extremely hazardous substances, as defined in 40 CFR 355, in threshold planning quantities, will be used, produced, stored, transported or disposed of in association with the drilling of this well.

EXHIBIT C
BOP DIAGRAM



NOTE: BOP side outlets may be used in place of drilling spool.




EXHIBIT D

WILDROSE RESOURCES CORPORATION
TROON FEDERAL #33-14
LEASE #U-74405
NW/SE SECTION 34, T9S, R18E
UINTAH COUNTY, UTAH

Thirteen Point Surface Use Program

Multipoint Requirements to Accompany APD

1. Existing Roads

- A. The proposed well site and elevation plat is shown on Exhibit A.
- B. From Myton, Utah, go west 1 mile. Turn south on Pleasant Valley road. Go south and east 18.1 miles. Turn south (right) for 2.1 miles. Turn east (left) 0.7 miles to location.
- C. See Exhibit E for access roads.
- D. There are no plans for improvement of existing roads. Roads will be maintained in present condition.

2. Planned Access Roads - (Newly Constructed)

- A. Length - 0.7 miles.
- B. Width - 30' right of way with 18' running surface maximum.
- C. Maximum grades - 2%
- D. Turnouts - N/A
- E. Drainage design - Barrow ditches and water turnouts as required.
- F. Culverts, bridges, cuts and fills - None.
- G. Surfacing material (source) - from location and access road.
- H. Gates, cattle guards and fence cuts - None.

All travel will be confined to existing access road rights of way.

Access roads and surface disturbing activities will conform to standards outlined in the Bureau of Land Management and Forest Service publication: Surface Operating Standards for Oil and Gas Exploration and Development, (1989).

The road shall be upgraded to meet the standards of the anticipated traffic flow and all weather road requirements. Construction/ upgrading shall include ditching, draining, graveling, crowning, and capping the roadbed as necessary to provide a well constructed safe road. Prior to upgrading, the road shall be cleared of any snow cover and allowed to dry completely. Traveling off the 30 foot right of way will not be allowed. Road drainage crossings shall be of the typical dry creek drainage crossing type. Crossings shall be designed so they will not cause siltation or accumulation of debris in the drainage crossing nor shall the drainages be blocked by the roadbed. Erosion of drainage ditches by runoff water shall be prevented by diversion water off at frequent intervals by means of cutouts. Upgrading shall not be allowed during muddy conditions. Should mud holes develop, they shall be filled in and detours around them avoided.

A Right of Way application is not needed.

3. Location of Existing Wells Within a 1 Mile Radius

See Exhibit G

- A. Water wells - none.
- B. Abandoned wells - none.
- C. Temporarily abandoned wells - none.
- D. Disposal wells - none.
- E. Drilling wells - none.
- F. Producing wells - none.
- G. Shut-in wells - none.
- H. Injection wells - none.

4. Location of Existing and/or Proposed Facilities

- A. On well pad - See Exhibit F for all production facilities to be used if well is completed as a producing oil well.
- B. Off well pad - N/A

If a tank battery is constructed on this lease, the battery or the well pad will be surrounded by a dike of sufficient capacity to

contain, at a minimum, the entire content of the largest tank within the battery, unless more stringent protective requirements are deemed necessary by the authorized officer.

Tank battery will be placed on the east side of the location.

All permanent (on site for six months or longer) structures constructed or installed (including pumping units) will be painted a flat, non-reflective, earthtone color to match one of the standard environmental colors, as determined by the Rock Mountain Five state Interagency Committee. All facilities will be painted within 6 months of installation. Facilities required to comply with O.S.H.A. (Occupational Safety and Health Act) will be excluded.

The required paint color is desert brown, 10YR.

If at any time the facilities located on public land and authorized by the terms of the lease are no longer included in the lease (due to a contraction in the unit or other lease or unit boundary change), BLM will process a change in authorization to the appropriate statute. The authorization will be subject to appropriate rental or other financial obligation as determined by the authorized officer.

5. Location and Type of Water Supply

- A. Water supply will be from Water Permit #43-1721 (Joe Shields spring).
- B. Water will be trucked across existing roads to location.
- C. No water wells to be drilled on lease.

6. Source of Construction Materials

- A. Native materials on lease will be used.
 - B. From Federal land.
 - C. N/A.
- A minerals material application is not required.

7. Methods for Handling Waste Disposal

- A.
 - 1) Drill cuttings will be buried in the reserve pit.
 - 2) Portable toilets will be provided for sewage.

3) Trash and other waste material will be contained in a trash cage and hauled away to an approved disposal site at the completion of the drilling activities.

4) Salts - if any will be disposed of.

5) Chemicals - if any will be disposed of.

B. Drilling fluids will be handled in the reserve pit. Any fluids produced during testing operations will be collected in a test tank. If a test tank is not available during drilling, fluids will be handled in the reserve pit. Any oil in the reserve pit will be removed.

Burning will not be allowed. All trash must be contained in trash cage and hauled away to an approved disposal site at the completion of drilling activities.

The reserve pit shall be constructed so as not to leak, break, or allow discharge.

Only if porous soils are encountered during the construction of the reserve pit and after inspection by a BLM representative, will a plastic nylon reinforced liner be used. If a plastic liner is used, it will be a minimum of 12 mil thickness with sufficient bedding (either straw or dirt) to cover any rocks. The liner will overlap the pit walls and be covered with dirt and/or rocks to hold it in place. No trash, scrap pipe, etc., that could puncture the liner will be disposed of in the pit. More stringent protective requirements may be deemed necessary by the A.O.

After first production, produced waste water will be confined to a lined pit or storage tank for a period not to exceed 90 days. During the 90 day period, in accordance with Onshore Order No. 7, an application for approval of a permanent disposal method and location, along with required water analysis, shall be submitted for the AO's approval. Failure to file an application within the time allowed will be considered an incident of noncompliance.

8. Ancillary Facilities

A. Camp facilities or airstrips will not be required.

9. Well Site Layout

A. See Exhibit H.

B. See Exhibit H.

C. See Exhibit H.

The reserve pit will be located on the south side of the

location.

The flare pit will be located downwind of the prevailing wind direction on the south side of the location a minimum of 100 feet from the well head and 30 feet from the reserve pit fence.

Topsoil - will be stored at the north side of the location.

Access to the well pad will be from the south east.

Fencing Requirements

All pits will be fenced according to the following minimum standards:

a. 39-inch net wire shall be used with at least one strand of barbed wire on top of the net wire (barbed wire is not necessary if pipe or some type of reinforcement rod is attached to the top of the entire fence).

b. The net wire shall be no more than 2-inches above the ground. The barbed wire shall be 3-inches above the net wire. Total height of the fence shall be at least 42-inches.

c. Corner posts shall be cemented and/or braced in such a manner to keep the fence tight at all times.

d. Standard steel, wood, or pipe posts shall be used between the corner braces. Maximum distance between any two posts shall be no greater than 16 feet.

e. All wire shall be stretched, by using a stretching device, before it is attached to the corner posts.

The reserve pit fencing will be on three sides during drilling operations and on the fourth side when the rig moves off the location. Pits will be fenced and maintained until clean-up.

10. Plans for Restoration of Surfaces

A. Producing Location:

Immediately upon well completion, the location and surrounding area will be cleared of all debris, materials, trash and junk not required for production.

Immediately upon well completion, any hydrocarbons on the pit shall be removed in accordance with 43 CFR 3162.7-1.

If a plastic nylon reinforced liner is used, it shall be torn

and perforated before backfilling of the reserve pit.

The reserve pit and that portion of the location not needed for production facilities/operations will be recontoured to the approximate natural contours. The reserve pit will be reclaimed within 120 days from the date of well completion. Before any dirt work takes place, the reserve pit must have all fluids and hydrocarbons removed and all cans, barrels, pipe, etc., will be removed.

The BLM will be contacted for required seed mixture.

B. Dry Hole/ Abandoned Location:

At such time as the well is plugged and abandoned, the operator will submit a subsequent report of abandonment and BLM will attach the appropriate surface rehabilitation conditions of approval.

11. Surface Ownership

Access Road: Federal
Location: Federal

12. Other Additional Information

A. The operator is responsible for informing all persons in the area who are associated with this project that they will be subject to prosecution for knowingly disturbing historic or archaeological sites, or for collecting artifacts. If historic or archaeological materials are uncovered during construction, the operator is to immediately stop work that might further disturb such materials, and contact the authorized officer (AO). Within five working days the AO will inform the operator as to:

- Whether the materials appear eligible for the National Register of Historic Places;

- The mitigation measures the operator will likely have to undertake before the site can be used (assuming in situ preservation is not necessary); and

- A time frame for the AO to complete an expedited review under 36 CFR 800.11 to confirm, through the State Historic Preservation Officer, that the findings of the AO are correct and that mitigation is appropriate.

If the operator wishes, at any time, to relocate activities to avoid the expense of mitigation and/or the delays associated with this process, the AO will assume responsibility for whatever recordation and stabilization of the exposed materials may be required. Otherwise, the operator will be responsible for

mitigation costs. The AO will provide technical and procedural guidelines for the conduct of mitigation. Upon verification from the AO that required mitigation has been completed, the operator will then be allowed to resume construction.

B. The operator will control noxious weeds along rights-of-way for roads, pipelines, well sites, or other applicable facilities. A list of noxious weeds may be obtained from the BLM, or the appropriate County Extension Office. On BLM administered land it is required that a Pesticide Use Proposal shall be submitted, and given approval, prior to the application of herbicides or other pesticides or possible hazardous chemicals.

C. Drilling rigs and/or equipment used during drilling operations on this wellsite will not be stacked or stored on Federal Lands after the conclusion of drilling operations or at any other time without BLM authorization. However, if BLM authorization is obtained, it is only a temporary measure to allow time to make arrangements for permanent storage on commercial facilities. (The BLM does not seek to compete with private industry. There are commercial facilities available for stacking and storing drilling rigs.)

Additional Surface Stipulations

Location will be moved 40' to the east at the time dirt work is done to avoid drainage ditch.

Cattleguard will be installed at fence line to be crossed by new access road. Fence will be properly brace prior to installing cattle guard.

Dirt contractor must meet with BLM representative on location prior to commencing dirt work.

Reclamation of unused disturbed areas on the well pad/access road no longer needed for operations, such as cut slopes, and fill areas will be accomplished by grading, leveling and seeding as recommended by the Authorized Officer.

13. Lessee's or Operators Representative and Certification Representative

Kary J. Kaltenbacher
Wildrose Resources Corporation
4949 South Albion Street
Littleton, CO 80121
Telephone: 303-770-6566

All lease and/or unit operations will be conducted in such a manner that full compliance is made with all applicable laws, regulations, Onshore Oil and Gas Orders, the approved plan of operations, and any applicable Notice to Lessees. The operator is fully responsible for the actions of his sub-contractors. A copy

of these conditions will be furnished to the field representative to insure compliance.

A complete copy of the approved APD and ROW grant, if applicable, shall be on location during construction of the location and drilling activities.

The operator or his/her contractor shall contact the BLM Office at (801) 789-1362 forty eight (48) hours prior to construction activities.

The BLM Office shall be notified upon site completion prior to moving on the drilling rig.


Self-Certification Statement:

Please be advised that Wildrose Resources Corporation is considered to be the operator of Troon Federal Well No. 33-14, NW/4 SE/4 of Section 14, Township 9 South, Range 18 East; Lease Number U-74405; Uintah County, Utah; and is responsible for the operations conducted upon the leased lands. Bond coverage is provided by Statewide Oil and Gas Bond No. 229352, Allied Mutual Insurance Company, approved by the BLM effective October 26, 1987.

Certification

I hereby certify that I, or persons under my direct supervision, have inspected the proposed drillsite and access route; that I am familiar with the conditions which currently exist; that the statements made in this plan are true and correct to the best of my knowledge; and, that the work associated with the operations proposed here will be performed by Wildrose Resources Corporation and its contractors and subcontractors in conformity with this plan and the terms and conditions under which it is approved. This statement is subject to the provisions of 18 U.S.C. 1001 for the filing of a false statement.

Date Aug. 13, 1996


Kary J. Kaltenbacher
Vice President

Onsite Date: August 6, 1996


Participants on Joint Inspection


Everett R. Wilcken
Byron Tolman

Wildrose Resources Corporation
BLM

CONFIDENTIAL STATEMENT

WILDROSE RESOURCES CORPORATION, AS OPERATOR, REQUESTS THAT ALL INFORMATION RELATED TO THIS WELL BE HELD TIGHT FOR THE MAXIMUM PERIOD ALLOWED BY FEDERAL AND STATE REGULATIONS.





TOPOGRAPHIC
MAP "B"
SCALE: 1"=2000'

Exhibit 'E-2'



WILDROSE RESOURCES CORP.

TROON FEDERAL #33-14
SECTION 14, T9S, R18E, S.L.B.&M.

2 Aug '96 83-123-026

PROPOSED PRODUCTION FACILITY DIAGRAM

VALVE DESCRIPTION		
	DURING PROD.	DURING SALES
VALVE #1	CLOSED	OPEN
VALVE #2	OPEN	CLOSED
VALVE #3	CLOSED	OPEN
VALVE #4	OPEN	CLOSED
VALVE #5	CLOSED	CLOSED
VALVE #6	CLOSED	CLOSED
VALVE #7	CLOSED	OPEN

DIKE





Exhibit 'F'



E


Exhibit 'G'

R 18 E




WILDROSE RESOURCES CORP.

WELL LAYOUT PLAT

TROON FEDERAL #33-14



LOCATED IN THE NW1/4 OF THE SE1/4 OF SECTION 14,
TOWNSHIP 9 SOUTH, RANGE 18 EAST, S.L.B.&M.



APPROXIMATE QUANTITIES

CUT: 5200 CU. YDS. (INCLUDES PIT)
FILL: 500 CU. YDS.

2 AUG 1996

83-123-026

Exhibit 'H'

JERRY D. ALLRED & ASSOCIATES
SURVEYING AND ENGINEERING CONSULTANTS

121 NORTH CENTER STREET
P.O. BOX 975
DUCHESTER, UTAH 84021
(801) 738-5352

WORKSHEET
APPLICATION FOR PERMIT TO DRILL

APD RECEIVED: 08/19/96

API NO. ASSIGNED: 43-047-32781

WELL NAME: TROON FEDERAL 33-14
OPERATOR: WILDROSE RESOURCES CORP (N9660)

PROPOSED LOCATION:
NWSE 14 - T09S - R18E
SURFACE: 1980-FSL-1843-FEL
BOTTOM: 1980-FSL-1843-FEL
UINTAH COUNTY
EIGHT MILE FLAT NORTH FIELD (590)

LEASE TYPE: FED
LEASE NUMBER: U-74405

PROPOSED PRODUCING FORMATION: GRRV

INSPECT LOCATION BY: / /

TECH REVIEW	Initials	Date
Engineering		
Geology		
Surface		

RECEIVED AND/OR REVIEWED:

☒ Plat
☒ Bond: Federal ☒ State ☐ Fee ☐
(Number 229352)
☒ Potash (Y/N)
☒ Oil shale (Y/N)
☒ Water permit
(Number 43-1721)
☒ RDCC Review (Y/N)
(Date: _____)


LOCATION AND SITING:

____ R649-2-3. Unit: _____
☒ R649-3-2. General.
____ R649-3-3. Exception.
____ Drilling Unit.
____ Board Cause no: _____
____ Date: _____

COMMENTS:

STIPULATIONS:

OPERATOR: WILDROSE RESOURCES
FIELD: EIGHT MILE FLAT NORTH
NUMBER: 590
COUNTY: UINTAH
UAC: R649-3-2



PREPARED:
DATE: 27-AUG-96

STATE OF UTAH, DIV OF OIL, GAS & MINERALS

Operator: WILDLROSE RESOURCES	Well Name: TROON FED 33-14
Project ID: 43-04732781	Location: SEC. 14 - T9S - R18E

Design Parameters:

Mud weight (8.80 ppg) : 0.457 psi/ft
 Shut in surface pressure : 2244 psi
 Internal gradient (burst) : 0.064 psi/ft
 Annular gradient (burst) : 0.000 psi/ft
 Tensile load is determined using air weight
 Service rating is "Sweet"

Design Factors:

Collapse : 1.125
 Burst : 1.00
 8 Round : 1.80 (J)
 Buttress : 1.60 (J)
 Other : 1.50 (J)
 Body Yield : 1.50 (B)

Casing Data									
Length (feet)		Size (in.)	Weight (lb/ft)	Grade	Joint	Depth (feet)	Drift (in.)	Cost	
1 5,700		5.500	15.50	J-55	ST&C	5,700	4.825		
	Collapse			Burst Load (psi)	Min Int Strgth (psi)	Yield S.F.	Tension		
	Load (psi)	Strgth (psi)	S.F.				Load (kips)	Strgth (kips)	S.F.
1	2606	4040	1.550	2606	4810	1.85	88.35	202	2.29 J

Prepared by : MATTHEWS, Salt Lake City, Utah
 Date : 09-05-1996
 Remarks :

GREEN RIVER

Minimum segment length for the 5,700 foot well is 1,500 feet.

SICP is based on the ideal gas law, a gas gravity of 0.75, and a mean gas

temperature of 114°F (Surface 74°F , BHT 154°F & temp. gradient 1.400°/100 ft.)

String type: Production

The mud gradient and bottom hole pressures (for burst) are 0.457 psi/ft and 2,606 psi, respectively.

NOTE: The design factors used in this casing string design are as shown above. As a general guideline, Lone Star Steel recommends using minimum design factors of 1.125 - collapse (with evacuated casing), 1.0 - (uniaxial) burst, 1.8 - API 8rd tension, 1.6 - buttress tension, 1.5 - body yield tension, and 1.6 - EUE 8rd tension. Collapse strength under axial tension was calculated based on the Westcott, Dunlop and Kemler curve. Engineering responsibility for use of this design will be that of the purchaser.
 Costs for this design are based on a 1987 pricing model. (Version 1.07)



State of Utah
DEPARTMENT OF NATURAL RESOURCES
DIVISION OF OIL, GAS AND MINING

Michael O. Leavitt
Governor

Ted Stewart
Executive Director

James W. Carter
Division Director

355 West North Temple
3 Triad Center, Suite 350
Salt Lake City, Utah 84180-1203
801-538-5340
801-359-3940 (Fax)
801-538-5319 (TDD)

September 5, 1996

Wildrose Resources Corporation
4949 South Albion Street
Littleton, Colorado 80121

Re: Troon Federal 33-14 Well, 1980' FSL, 1843' FEL, NW SE,
Sec. 14, T. 9 S., R. 18 E., Uintah County, Utah

Gentlemen:

Pursuant to the provisions and requirements of Utah Code Ann. 40-6-1 et seq., Utah Administrative Code R649-3-1 et seq., and the attached Conditions of Approval, approval to drill the referenced well is granted.

This approval shall expire one year from the above date unless substantial and continuous operation is underway, or a request for extension is made prior to the expiration date. The API identification number assigned to this well is 43-047-32781.

Sincerely,

R. J. Firth
Associate Director

lwp

Enclosures

cc: Uintah County Assessor
Bureau of Land Management, Vernal District Office

Operator: Wildrose Resources Corporation
Well Name & Number: Troon Federal 33-14
API Number: 43-047-32781
Lease: U-74405
Location: NW SE Sec. 14 T. 9 S. R. 18 E.

Conditions of Approval

1. General

Compliance with the requirements of Utah Admin. R. 649-1 et seq., the Oil and Gas Conservation General Rules, and the applicable terms and provisions of the approved Application for Permit to Drill.

2. Notification Requirements

Notify the Division within 24 hours following spudding the well or commencing drilling operations. Contact Jimmie Thompson at (801)538-5336.

Notify the Division prior to commencing operations to plug and abandon the well. Contact Frank Matthews at (801)538-5334 or Mike Hebertson at (801)538-5333.

3. Reporting Requirements

All required reports, forms and submittals shall be promptly filed with the Division, including but not limited to the Entity Action Form (Form 6), Report of Water Encountered During Drilling (Form 7), Weekly Progress Reports for drilling and completion operations, and Sundry Notices and Reports on Wells requesting approval of change of plans or other operational actions.


UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. TYPE OF WORK DRILL <input checked="" type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. U-74405
b. TYPE OF WELL OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> SINGLE ZONE <input checked="" type="checkbox"/> MULTIPLE ZONE <input type="checkbox"/>		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
2. NAME OF OPERATOR Wildrose Resources Corporation PH: 303-770-6566		7. UNIT AGREEMENT NAME
3. ADDRESS OF OPERATOR 4949 South Albion Street, Littleton, CO 80121		8. FARM OR LEASE NAME Troon Federal
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)* At surface 1980' FSL & 1843' FEL (NW $\frac{1}{4}$ SE $\frac{1}{4}$) At proposed prod. zone Same		9. WELL NO. 33-14
14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE* 21 miles SE of Myton, Utah		10. FIELD AND POOL, OR WILDCAT Eight Mil Flat
10. DISTANCE FROM PROPOSED* LOCATION TO NEAREST PROPERTY OR LEASE LINE, FT. (Also to nearest drlg. unit line, if any) 1843'	16. NO. OF ACRES IN LEASE 1200	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 14, T9S, R18E
18. DISTANCE FROM PROPOSED LOCATION* TO NEAREST WELL, DRILLING, COMPLETED, OR APPLIED FOR, ON THIS LEASE, FT. None	17. NO. OF ACRES ASSIGNED TO THIS WELL 40	12. COUNTY OR PARISH Uintah
21. ELEVATIONS (Show whether DF, RT, GR, etc.) 4931' GR	19. PROPOSED DEPTH 5700'	13. STATE Utah
20. ROTARY OR CABLE TOOLS Rotary		22. APPROX. DATE WORK WILL START* September 15, 1996

23. PROPOSED CASING AND CEMENTING PROGRAM				
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
12-1/4"	8-5/8"	24#, J-55	300'	225 sx
7-7/8"	5-1/2"	15.5#, J-55	5700'	800 sx

SEE ATTACHED EXHIBITS: A - Surveyors Plat E - Access Road Map
B - 10 Point Plan F - Production Facilities
C - BOP Diagram G - Existing Wells Map
D - 13 Point Surface Use Program H - Pit & Pad Layout, Cuts & Fills, Cross Sections, Rig Layout



AUG 1996
Received
DOI-BLM
Vernal, Utah

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present productive zone and proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true vertical depths. Give blowout preventer program, if any.

24. SIGNED Kary J. Keltner TITLE Vice President DATE August 13, 1996

(This space for Federal or State office use)

NOTICE OF APPROVAL

PERMIT NO. _____ ACTING APPROVAL DATE _____
Assistant Field Manager
APPROVED BY [Signature] TITLE Mineral Resources DATE SEP 05 1996
CONDITIONS OF APPROVAL, IF ANY: _____

CONDITIONS OF APPROVAL ATTACHED
TO OPERATOR'S COPY

*See Instructions On Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

U+080-6m-198

CONDITIONS OF APPROVAL
APPLICATION FOR PERMIT TO DRILL

Company/Operator: Wildrose Resources Corporation

Well Name & Number: Troon Fed. 33-14

API Number: 43-047-32781

Lease Number: U-74405

Location: NWSE Sec. 14 T. 09S R. 18E

NOTIFICATION REQUIREMENTS

- | | | |
|---------------------------------|---|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Location Construction | - | at least forty-eight (48) hours prior to construction of location and access roads. |
| Location Completion | - | prior to moving on the drilling rig. |
| Spud Notice | - | at least twenty-four (24) hours prior to spudding the well. |
| Casing String and Cementing | - | at least twenty-four (24) hours prior to running casing and cementing all casing strings. |
| BOP and Related Equipment Tests | - | at least twenty-four (24) hours prior to initiating pressure tests. |
| First Production Notice | - | within five (5) business days after new well begins, or production resumes after well has been off production for more than ninety (90) days. |

For more specific details on notification requirements, please check the Conditions of Approval for Notice to Drill and Surface Use Program.

CONDITIONS OF APPROVAL FOR NOTICE TO DRILL

Approval of this application does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

All lease and/or unit operations will be conducted in such a manner that full compliance is made with applicable laws, regulations (43 CFR 3100), Onshore Oil and Gas Orders, and the approved plan of operations. The operator is fully responsible for the actions of his subcontractors. A copy of these conditions will be furnished the field representative to insure compliance.

Be aware fire restrictions may be in effect when location is being constructed and/or when well is being drilled. Contact the appropriate Surface Management Agency for information.

A. DRILLING PROGRAM

1. Estimated Depth at Which Oil, Gas, Water, or Other Mineral Bearing Zones are Expected to be Encountered

Report **ALL** water shows and water-bearing sands to Tim Ingwell of this office **prior to setting the next casing string or requesting plugging orders**. Faxed copies of State of Utah form OGC-8-X are acceptable. If noticeable water flows are detected, submit samples to this office along with any water analyses conducted.

All usable water and prospectively valuable minerals (as described by BLM at onsite) encountered during drilling, will be recorded by depth and adequately protected. All oil and gas shows will be tested to determine commercial potential.

2. Pressure Control Equipment

The BOP and related equipment shall meet the minimum requirements of Onshore Oil and Gas Order No. 2 for equipment and testing requirements, procedures, etc., for a **2M** system and individual components shall be operable as designed. Chart recorders shall be used for all pressure tests.

Test charts, with individual test results identified, shall be maintained on location while drilling and shall be made available to a BLM representative upon request.

If an air compressor is on location and is being utilized to provide air for the drilling medium while drilling, the special drilling requirements in Onshore Oil and Gas Order No. 2, regarding air or gas drilling shall be adhered to. If a mist system is being utilized then the requirement for a deduster shall be waived.

3. Casing Program and Auxiliary Equipment

If conductor pipe is set it shall be cemented to surface. If drive pipe is used it shall be pulled prior to cementing surface casing.

Surface casing shall have centralizers on the bottom three joints, with a minimum of one centralizer per joint.

As a minimum, the usable water and oil shale resources shall be isolated and/or protected by having a cement top for the production casing at least 200 ft. above the Usable Water Zone, identified at \pm 846 ft. If gilsonite is encountered while drilling, it shall be isolated and/or protected via the cementing program.

4. Mud Program and Circulating Medium

Hazardous substances specifically listed by the EPA as a hazardous waste or demonstrating a characteristic of a hazardous waste will not be used in drilling, testing, or completion operations.

No chromate additives will be used in the mud system on Federal and Indian lands without prior BLM approval to ensure adequate protection of fresh water aquifers.

5. Coring, Logging and Testing Program

Daily drilling and completion progress reports shall be submitted to this office on a weekly basis.

All Drill Stem tests (DST) shall be accomplished during daylight hours, unless specific approval to start during other hours is obtained from the AO. However, DSTs may be allowed to continue at night if the test was initiated during daylight hours and the rate of flow is stabilized and if adequate lighting is available (i.e., lighting which is adequate for visibility and vaporproof for safe operations). Packers can be released, but tripping should not begin before daylight unless prior approval is obtained from the AO.

A cement bond log (CBL) will be run from the production casing shoe to \pm 646 ft. and shall be utilized to determine the bond quality for the production casing. Submit a field copy of the CBL to this office.

Whether the well is completed as a dry hole or as a producer, "Well Completion and Recompletion Report and Log" (Form 3160-4) will be submitted not later than 30 days after completion of the well or after completion of operations being performed, in accordance with 43 CFR 3164. Two copies of all logs, core descriptions, core analyses, well-test data, geologic summaries, sample description, and all other surveys or data obtained and compiled during the drilling, workover, and/or completion operations, will be filed with Form 3160-4. Samples (cuttings, fluids, and/or gases) will be submitted when requested by the AO.

6. Notifications of Operations

No location will be constructed or moved, no well will be plugged, and no drilling or workover equipment will be removed from a well to be placed in a suspended status without prior approval of the AO. If operations are to be suspended, prior approval of the AO will be obtained and notification given before resumption of operations.

The Vernal District Office shall be notified, during regular work hours (7:45 a.m.-4:30 p.m., Monday through Friday except holidays), at least 24 hours **prior** to spudding the well.

Operator shall report production data to MMS pursuant to 30 CFR 216.5 using form MMS/3160.

Immediate Report: Spills, blowouts, fires, leaks, accidents, or any other unusual occurrences shall be promptly reported in accordance with the requirements of NTL-3A or its revision.

If a replacement rig is contemplated for completion operations, a "Sundry Notice" (Form 3160-5) to that effect will be filed, for prior approval of the AO, and all conditions of this approved plan are applicable during all operations conducted with the replacement rig.

The date on which production is commenced or resumed will be construed for oil wells as the date on which liquid hydrocarbons are first sold or shipped from a temporary storage facility, such as a test tank, and for which a run ticket is required to be generated or, the date on which liquid hydrocarbons are first produced into a permanent storage facility, whichever first occurs; and, for gas wells as the date on which associated liquid hydrocarbons are first sold or shipped from a temporary storage facility, such as a test tank, and for which a run ticket is required to be generated or, the date on which gas is first measured through permanent metering facilities, whichever first occurs.

Should the well be successfully completed for production, the AO will be notified when the well is placed in a producing status. Such notification will be sent by telegram or other written communication, not later than five (5) days following the date on which the well is placed on production.

Gas produced from this well may not be vented or flared beyond an initial authorized test period of 30 days or 50 MMCF following its completion, whichever occurs first, without the prior written approval of the Authorized Officer. Should gas be vented or flared without approval beyond the authorized test period, the operator may be directed to shut-in the well until the gas can be captured or approval to continue venting or flaring as uneconomic is granted and the operator shall be required to compensate the lessor for that portion of the gas vented or flared without approval which is determined to have been avoidably lost.

A schematic facilities diagram as required by 43 CFR 3162.7-5 (b.9. d.), and shall be submitted to the appropriate District Office within sixty (60) days of installation or first production, whichever occurs first. All site security regulations as specified in Onshore Oil & Gas Order No. 3 shall be adhered to. All product lines entering and leaving hydrocarbon storage tanks will be effectively sealed in accordance with 43 CFR 3162.7-5 (b. 4).

No well abandonment operations will be commenced without the prior approval of the AO. In the case of newly drilled dry holes or failures, and in emergency situations, oral approval will be obtained from the AO. A "Subsequent Report of Abandonment" Form 3160-5, will be filed with the AO within thirty (30) days following completion of the well for abandonment. This report will indicate where plugs were placed and the current status of surface restoration. Final abandonment will not be approved until the surface reclamation work required by the

approved APD or approved abandonment notice has been completed to the satisfaction of the AO or his representative, or the appropriate Surface Managing Agency.

7. Other Information

All loading lines will be placed inside the berm surrounding the tank battery.

All off-lease storage, off-lease measurement, or commingling on-lease or off-lease will have prior written approval from the AO.

The oil and gas measurement facilities will be installed on the well location. The oil and gas meters will be calibrated in place prior to any deliveries. Tests for meter accuracy will be conducted following initial installation and at least quarterly thereafter. The AO will be provided with a date and time for the initial meter calibration and all future meter proving schedules. A copy of the meter calibration reports will be submitted to the Vernal District Office. All meter measurement facilities will conform with Onshore Oil & Gas Order No. 4 for liquid hydrocarbons and Onshore Oil & Gas Order No. 5 for natural gas measurement.

The use of materials under BLM jurisdiction will conform to 43 CFR 3610.2-3.

There will be no deviation from the proposed drilling and/or workover program without prior approval from the AO. Safe drilling and operating practices must be observed. All wells, whether drilling, producing, suspended, or abandoned will be identified in accordance with 43 CFR 3162.

"Sundry Notice and Report on Wells" (Form 3160-5) will be filed for approval for all changes of plans and other operations in accordance with 43 CFR 3162.3-2.

Section 102(b)(3) of the Federal Oil and Gas Royalty Management Act of 1982, as implemented by the applicable provisions of the operating regulations at Title 43 CFR 3162.4-1(c), requires that "not later than the 5th business day after any well begins production on which royalty is due anywhere on a lease site or allocated to a lease site, or resumes production in the case of a well which has been off production for more than 90 days, the operator shall notify the authorized officer by letter or sundry notice, Form 3160-5, or orally to be followed by a letter or sundry notice, of the date on which such production has begun or resumed."

If you fail to comply with this requirement in the manner and time allowed, you shall be liable for a civil penalty of up to \$10,000 per violation for each day such violation continues, not to exceed a maximum of 20 days. See Section 109(c)(3) of the Federal Oil and Gas Royalty Management Act of 1982 and the implementing regulations at Title 43 CFR 3162.4-1(b)(5)(ii).

APD approval is valid for a period of one (1) year from the signature date. An extension period may be granted, if requested, prior to the expiration of the original approval period.

In the event after-hours approval or notification is necessary, please contact one of the following individuals:

Wayne P. Bankert (801) 789-4170
Petroleum Engineer

Ed Forsman (801) 789-7077
Petroleum Engineer

Jerry Kenczka (801) 789-1190
Petroleum Engineer

BLM Fax Machine (801) 781-4410

EPA'S LIST OF NONEXEMPT EXPLORATION AND PRODUCTION WASTES

While the following wastes are nonexempt, they are not necessarily hazardous.

- Unused fracturing fluids or acids
- Gas plant cooling tower cleaning wastes
- Painting wastes
- Oil and gas service company wastes, such as empty drums, drum rinsate, vacuum truck rinsate, sandblast media, painting wastes, spent solvents, spilled chemicals, and waste acids
- Vacuum truck and drum rinsate from trucks and drums, transporting or containing nonexempt waste
- Refinery wastes
- Liquid and solid wastes generated by crude oil and tank bottom reclaimers
- Used equipment lubrication oils
- Waste compressor oil, filters, and blowdown
- Used hydraulic fluids
- Waste solvents
- Waste in transportation pipeline-related pits
- Caustic or acid cleaners
- Boiler cleaning wastes
- Boiler refractory bricks
- Incinerator ash
- Laboratory wastes
- Sanitary wastes
- Pesticide wastes
- Radioactive tracer wastes
- Drums, insulation and miscellaneous solids.

CONDITIONS OF APPROVAL
FOR THE SURFACE USE PROGRAM OF THE
APPLICATION FOR PERMIT TO DRILL

- The location should be moved 40 feet to the east in order to avoid the drainage.
- A 16' x 8' cattle guard should be installed where the road passes through the fence. The cattle guard should be installed on cement bases. It is not necessary to install a gate in the fence next to the cattle guard, since a gate is present just to the south already. The fence should be braced prior to cutting the wire where the cattle guard will be installed.
- The topsoil should be windrowed along the entire north side of the location between corners 2 and 8.

CONFIDENTIAL
CONFIDENTIAL

DIVISION OF OIL, GAS AND MINING

SPUDDING INFORMATION

Name of Company: WILDROSE

Well Name: TROON FEDERAL 33-14

Api No. 43-047-32781

Section 14 Township 9S Range 18E County UINTAH

Drilling Contractor CAZA

Rig #: 56

SPUDDED:

Date: 10/7/96

Time: 2:00 PM

How: DRY HOLE

Drilling will commence: _____

Reported by: CARY KALTENBACHER

Telephone #: _____

Date: 10/8/96 Signed: JLT

3270 ✓

ENTITY ACTION FORM - FORM 6

OPERATOR WILDROSE RESOURCES CORP
ADDRESS 4949 So. Albion St.
Littleton, CO 80121

OPERATOR ACCT. NO. N 9660


ACTION CODE	CURRENT ENTITY NO.	NEW ENTITY NO.	API NUMBER	WELL NAME	WELL LOCATION					SPUD DATE	EFFECTIVE DATE
					QQ	SC	TP	RG	COUNTY		
A	99999	12018	4304732781	Troon Federal 33-14	NW/SE	14	95	18E	Uintah	10/7/96	
WELL 1 COMMENTS: Entity added 10-22-96. <i>lec</i>											
WELL 2 COMMENTS:											
WELL 3 COMMENTS:											
WELL 4 COMMENTS:											
WELL 5 COMMENTS:											

ACTION CODES (See instructions on back of form)

- A - Establish new entity for new well (single well only)
- B - Add new well to existing entity (group or unit well)
- C - Re-assign well from one existing entity to another existing entity
- D - Re-assign well from one existing entity to a new entity
- E - Other (explain in comments section)

NOTE: Use COMMENT section to explain why each Action Code was selected.

(3/89)



Kary Kallenberg
Signature
V.P.
Title
10/15/96
Date
Phone No. 303, 770-6566

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CONFIDENTIAL

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: September 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☒ Other **Dry**

2. Name of Operator

Wildrose Resources Corp. 303-770-6566

3. Address and Telephone No.

4949 S. Albion St., Littleton, CO 80121

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

**1980' FSL # 1943' FEL (NW/SE)
Section 14, T9S, R18E**

5. Lease Designation and Serial No.

U-74405

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Troon Fed. 33-14

9. API Well No.

43-047-32781

10. Field and Pool, or Exploratory Area

Eight mile Flat North

11. County or Parish, State

Uintah County, Utah

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was P&A'd on November 2, 1996 as follows:

Plug #1: 4445' - 4165': 88 sx Class 'G' w/ 2% CaCl₂

Tagged plug #1 @ 4167' after 4 hrs.

Plug #2: 995' - 763': 80 sx Class 'G'

Lost returns while pumping Plug #2. WOC 4 hrs. Could not tag Plug #2.

Plug #3: 995' - 763': 80 sx Class 'G' w/ 3% CaCl₂ & 1/4#/sk floccle.

Fluid level stayed at surface after pumping Plug #3.

Plug #4: 395' - 0': 142 sx Class 'G'

Drilling fluid (2% KCl water - 8.3 ppg) was used to displace plugs.

Dry hole marker has been installed and location has been rehab'd except for seeding.

14. I hereby certify that the foregoing is true and correct

Signed **Kary Kallenberg**

Title **V.P.**

Date **11/22/96**

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CONFIDENTIAL

Form approved.
Budget Bureau No. 1004-0137
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

U-74405

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Troon Federal

9. WELL NO.

33-14

10. FIELD AND POOL, OR WILDCAT

Eight mile Flat North

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 14, T9S, R18E

12. COUNTY OR PARISH

Utah

13. STATE

Utah

WELL COMPLETION OR RECOMPLETION REPORT AND LOG *

1a. TYPE OF WELL: OIL WELL ☒ GAS WELL ☐ DRY ☒ Other ☐

b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RENVR. ☐ Other ☐

2. NAME OF OPERATOR

Wildrose Resources Corp.

3. ADDRESS OF OPERATOR

4949 S. Albion St, Littleton, CO 80121

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface 1980' FSL & 1843' FEL (NW/SE)

At top prod. interval reported below Same

At total depth Same

14. PERMIT NO.

43-047-32781

DATE ISSUED

15. DATE SPURRED

10/7/96

16. DATE T.D. REACHED

10/31/96

17. DATE COMPL. (Ready to prod.)

11/2/96 P3A

18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*

4931' GR

19. ELEV. CASINGHEAD

-

20. TOTAL DEPTH, MD & TVD

5800'

21. PLUG, BACK T.D., MD & TVD

22. IF MULTIPLE COMPL., HOW MANY*

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

0'-TD

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*

25. WAS DIRECTIONAL SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

MUD LOG DIL, FDC-CNL 12-9-96

27. WAS WELL CORRED

No

CONFIDENTIAL

28. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8	24	306'	12 1/4	120 SX (to surface)	None

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)

31. PRODUCTION RECORD (Flowing, gas lift, pumping—size and type of pump)	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.	
	DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
32. DIV. OF OIL, GAS & MINING	DEC 0 0 1996	
	DEC 0 0 1996	
33. DIV. OF OIL, GAS & MINING	DEC 0 0 1996	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

TEST WITNESSED BY

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)	

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

Logs, Daily Reports

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE

V.P.

DATE

11/22/96

*(See Instructions and Spaces for Additional Data on Reverse Side)

37. SUMMARY OF POROUS ZONES: (Show all important zones of porosity and contents thereof; cored intervals; and all drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries):

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.	NAME	TOP	
					MEAS. DEPTH	TRUE VERT. DEPTH
				Green River	1273'	1273'
				Wasatch Tongue	5575'	5575'

38. GEOLOGIC MARKERS

DAILY DRILLING REPORT

CONFIDENTIAL

Operator: Wildrose Resources Corporation
Well: #33-14 Troon Federal
T 9 S, R 18 E, Section 14
NW SE (1980' FSL & 1843' FEL)
Uintah County, Utah
Projected TD - 5700'
Elevation: GR: 4929', KB: 4942' estimated
Contractor: Caza Rig #56

10/08/96 MI & RU Ross Well Service air rig. Spudded @ 2:00 PM 10/07/96. Drilled 150' of 12 1/4" hole. SDFN.

10/09/96 Drilled to 302'. SDFN.

10/10/96 Ran 7 jts (292') 8 5/8" 24# J-55 STC csg w/ guide shoe & 3 centralizers. Set csg @ 306' KB. Pumped 45 bbl water. Cemented w/ 120 sx Class 'G' cement w/ 2% gel, 2% CaCl₂, & 1/4#/sk Flocele & 25 sx Class 'G' w/ 2% CaCl₂. Dropped plug. Displaced w/ 16 bbl water. Had good cement to surface. SDFN.

10/11/96 Drill mouse & rat hole. RD & MO.

10/27/96 MI Caza Rig #56. Work on rig.

10/28/96 Day 1: TD-1400' drlg. Drld 1100' in 13 3/4 hrs w/ water. RU. Tested BOP's to 2000 psi. Ran Bit #1 7 7/8", HTC, ATJ22 @ 300'. Surveys: 1' @ 805', 1 1/4' @ 1329'.

10/29/96 Day 2: TD-2960' drlg. Drld 1560' in 22 1/2 hrs w/ water. Bit #1 has drld 2660' in 36 1/4 hrs. Surveys: 3/4' @ 1881', 1/2' @ 2389', 2' @ 2889'.

10/30/96 Day 3: TD-4008' drlg. Drld 1048' in 16 hrs w/ 2% KCl water. Pulled Bit #1 @ 2987'. Bit #1 drld 2687' in 36 hrs. Ran Bit #2, 7 7/8", STC, F3H @ 2987'. Bit #2 has drld 1021' in 15 1/2 hrs. Surveys: 2 1/4' @ 3387', 2' @ 3855'.

10/31/96 Day 4: TD-5131' drlg. Drld 1113' in 22 1/2 hrs w/ 2% KCl water. Bit #2 had drld 2134' in 38 hrs. Survey: 1 1/4' @ 4378', 2' @ 4907'.

11/01/96 Day 5: TD-5800' logging. Drld 679' in 15 hrs w/ 2% KCl water. Pulled Bit #2 @ 5800'. Bit #2 drld 2813' in 53 hrs.

11/02/96 Day 6: TD-5800' plugging. WOC. Ran logs using Schlumberger as follows:

ARI/DLL 5783' - 306'

FDC/CNL 5777' - 3300'

Logger's TD - 5795'. RD Schlumberger. WOC. TIH w/ collars. LD collars. TIH w/ DP. LDDP to 4445'. Circulate for 1 hr. RU HOWCO. Pumped 10 BW, 88 sx Class 'G' w/ 2% CaCl₂ & 3 BW. Displaced w/ 55 bbl drilling fluid.

Plug #1: 4445'-4165' (88 sx). Pulled 10 stds. Circulated & WOC 4 hrs. Ran 6 stds. Tagged plug @ 4167'. Pulled 2 stds. Broke circulation. LDDP to 995'. RU HOWCO. Pumped 10 BW, 80 sx Class 'G' cement & 3 BW. Displaced w/ 7 bbl drlg fluid.

Plug #2: 995'-763' (80 sx). Lost returns while pumping plug #2. Now WOC.

11/03/96 Day 7: TD-5800'. P & A'd. WOC on plug #2 for 4 hrs. TIH w/ 10 stds - did not tag plug. RU HOWCO. Pumped 10 BW, 80 sx Class 'G' w/ 3% CaCl₂ & 1/4#/sk Flocele & 3 BW. Displaced w/ 7 bbl drilling fluid.

Plug #3: 995'-763' (80 sx). Pulled 6 stds. LDDP. Ran 1 jt + 6 stds to 395'. Circulated cement to surface w/ 142 sx Class 'G'.

Plug #4: 395'-0' (142 sx). LD 13 jts DP. Topped off cement. RD HOWCO. Released rig @ 12 PM 11/2/96. Drop from report.